

## Solar Inverters On Grid-15kW Sunipod ONG-15kW

Solar Inverters specifically designed for on grid operations.



### HIGHLIGHTS

#### Electrical Environment Friendly

- Galvanic isolation of DC input and AC output using output transformer specifically for grid tie installations.
- Intelligent MPPT Tracking.

#### Industry-Leading Reliability

- Endurance tested to 20 year operating life.
- Lowest part counts and fewest interconnects eliminate common failure points.
- Field-proven technology.

#### Integrated AC and DC PV System Disconnect

- As per UL 98 Standard for use with input strings.
- NEC Compliant internal wire raceway enables side-by-side mounting.
- Direct-to-wall surface enclosure design allows for easy access and installation.

#### State-of-the-art display

- Complete view of inverter operation.

#### Easy Installation

- Factory integrated inverter and PV System Disconnect eliminates the need for extra equipment.
- Integrated disconnect reduces conduit connection points saving installation time and material cost.
- Field-configurable positive/negative ground applications.
- Optimally placed knockouts for a variety of conduit routing options.

#### Installer-Focused Support

- No special purchase requirements to get the best technical support in the industry.
- Technical phone support.
- Economical performance monitoring options.

**SPECIFICATIONS**

	<b>ONG-15kW</b>
<b>Electrical Specifications</b>	
Continuous Output Power (W)	15000W
Weighted CEC Efficiency	92
Maximum DC Input Voltage (V)	600VDC
DC Maximum Input Current (A)	75.0 A
AC Rated Output Current (A)	66.0 A
AC Nominal Output Voltage (V)	230V
AC Nominal Output Frequency (Hz)	50Hz
Output Waveform Shape	Sinewave
Output Harmonic Distortion (%)	Less than 3%
AC Output Voltage Range (V)	±3%
AC Output Frequency Range (Hz)	±1%
MPPT based Tracker	Yes
<b>Mechanical Specifications</b>	
Temperature	-10 °C to 60 °C
Humidity	0 to 98%
Cooling	Free convection
Communication	GSM Wireless GPRS/3G
Weight with Disconnects	135 Kgs
Inverter with Disconnects	
Dimensions (L X W X D)	60inch X 36inch X 24inch
<b>Standards/Safety Specifications</b>	
Protection Degree	IP65
System Disconnect	Inverter with Factory-Integrated AC and DC PV System Disconnect
Enclosure	NEMA 3R Steel Enclosure, Wall Mounted with Bracket Included
Overload Behavior	Current Limitation, Power Limitation
Anti-Islanding	Yes

- Three Phase Solar Inverters can be provided on request.

**APPLICATIONS:**

- Diesel Generator Alternative Using Solar Power Plants
- Lower Your Electric Bill Using Solar Power Stations

Specifications included in this datasheet are subject to change without notice. Electric data without guarantee.

**Contact India Office:**

Victory Mansion, Sitaladevi Temple Road, Mahim, Mumbai – 400016  
Ph: 022-6464-9090

**Contact US Office:**

509 Granger Terrace, Sunnyvale, CA – 94087  
Ph: +1-408-431-0408

